

SCREEN PRODUCTS

- USING AGEING SPRAYS -

General Spraying

Hold can approximately 300mm away from the surface to be sprayed and depress the button to release the spray. To obtain an even covering, move your hand in a continuous motion keeping it the same distance from the surface. The more times an area is sprayed the denser the covering and the darker the effect. (If you do need a darker finish, it may be better to apply a number of thin coatings rather than a single thick coat).

Finer More Detailed Spraying

For finer work, press the button more gently to release less spray. (The harder the button is depressed the more spray is released). Hold the can closer to the surface and press the button more lightly

Variable / Patchy Spraying

For variable/patchy surface covering, move the can more slowly across the surface at different speeds, slowing over areas where the spray is to be more concentrated.

General Information

If the spray is concentrated on an area for too long, too much dye may gather causing it to run. It is best to build up a denser covering by applying more layers rather than concentrating the spray on one fixed place. When Dirty Down is dry, it can leave a slight powder residue which can be rubbed to make it smudge. It is easier to smudge dry Dirty Down if it is rubbed with a wetter cloth. Dirty Down dyes can be washed off certain surfaces, but in a lot of cases will cause permanent stains. Always test the spray on a small area before use. Dirty Down will change colour as it dries. The final colour is only achieved after the spray is fully dry. The colour will also change depending on the amount of spray applied. Always read the safety data sheets before use.

Tel: Alan - 07926 196 471

Dirty
Down

www.dirtydown.co.uk